

LIPPELIFT T80

PLATFORM FOR WHEELCHAIRS ON STAIRS WITH CURVES.



TECHNICAL INFORMATION:

LIFTING CAPACITY:	300 Kg
PLATFORM DIMENSIONS:	Standard W x L: 800 x 1000 mm (or 680 x 480mm/ 700 x 900 mm/ 750 x 1000 mm) (Other dimensions possible up to 900 x 1200 mm)
MIN. WIDTH PLATFORM UP:	518 mm
MIN. WIDTH PLATFORM OPEN:	1153 mm
MIN. WIDTH STAIRCASE:	1200 mm
GRADIENT:	min. 0° to max. 60°
SPEED:	max. 0,15m/s
TRACTION:	DC-motor with gearbox and chaintraction
GUIDE RAILS:	Double rail: seamless drawn steel tube profile
TRACTIONMOTOR:	monofase 230 V/ 16 Amp + ground wire
MOTOR PLATFORM:	24V / DC
MOTOR ARMS:	24V / DC
ATTENDANCE:	Hold-to-run
COLOR PLATFORM, AND RAILS:	Choice of 6 standard RAL-colors: RAL7032, RAL7047, RAL8022, RAL9002, RAL9006, en RAL9007

Foreseen of a CE-declaration following the new machine directive 2006/42/EC